
Remove Residual Magnetism

'C' Type Demagnetizer

MagTECH ASSOCIATES
SINCE1996
Manufacturing Magnetic Product as per Clients Requirements





Application

Demagnetizer is designed to eliminate Residual Magnetism of work piece, which is generated due to manufacturing process like turning milling grinding operations and due to contact with magnet also. Sizes and models are varying as per requirement. Magnetism can be verified by the GAUSS METER.

This particular model is for on line conveyor system.

How to operate

a) Provide a suitable supply to demagnetizer.
b) It is operated by the Foot Switch and can also be operated by Programable Logic Control panel (PLC) The work piece is passed through tunnel.

How to check performance

a) Check residual magnetism of work piece by Residual Field meter (Gauss Meter). BEFORE demagnetizing.
b) Demagnetize it as per above instructions.
c) Check residual magnetism of work piece by Residual Field meter (Gauss Meter)AFTER demagnetizing.

Area of application

On line conveyor system,Tool Room, Standard Room, Press Shop, Assembly line etc.

Advantages

Increases tool life. Increases productivity. Increases quality.

Available sizes

Model Code No.	Aperture Size (L x W x H)
023-05-01	L150 x W100 x H100mm

Magtech Associates



Control Panel for Demagnetizer

Tel. : (020) 2749 09 53, **Mob** : +91 9850 08 69 39 (Yogesh Naik) **Email** : yogeshnaik@magtechassociates.com, magyog@gmail.com,
Website : www.magtechassociates.com, www.demagnetizerpune.com